

TEMPERING & DRAIN TANK

Aseptic tank with double jacket and bottom outlet

Material

1.4404 (316L)

Finishing

electropolished inside and outside

Volumes

0.1 to 200 liters (see type overview)

Gaskets

EPDM, silicone or PTFE

Pressure

-1/+5 bar

Other

GMP-compliant documentation

Equipment

Central Tri-Clamp nozzle with:

- **OUT** Immersion tube with Tri-Clamp connection
- **GAS** pipe bend with Tri-Clamp connection

Above cylindrical part and bottom:

- **DOUBLE MANTLE**

Centered in the underbody:

- **DRAIN** floor outlet in 90° bend with Tri-Clamp connection



Type	Material	Finishing	Volume [l]	Ø Da [mm]	H [mm]	s [mm]	Mass [kg]	Pressure [bar]
JCDS 0.25	1.4404 (316L)	electropolished	0,3	67	300	1	3	-1/+5
JCDS 0.5	1.4404 (316L)	electropolished	0,6	89	330	1	4	-1/+5
JCDS 01	1.4404 (316L)	electropolished	1,3	108	350	1	4	-1/+5
JCDS 02	1.4404 (316L)	electropolished	3	140	425	1	6	-1/+5
NCDS 05	1.4404 (316L)	electropolished	6	181	480	1,5	7	-1/+5
NCDS 10	1.4404 (316L)	electropolished	12	229	600	1,5	9	-1/+5
NCDS 20	1.4404 (316L)	electropolished	22	278	700	1,5	17	-1/+5
HCDS 30	1.4404 (316L)	electropolished	33	324	750	2	24	-1/+5
HCDS 50	1.4404 (316L)	electropolished	53	363	900	2	31	-1/+5
HCDS 100	1.4404 (316L)	electropolished	110	450	1050	2	53	-1/+4
MCDS 150	1.4404 (316L)	electropolished	160	550	1050	2,5	66	-1/+4
HCDS 200	1.4404 (316L)	electropolished	205	550	1200	2	75	-1/+4

Safety for people, product and the environment



Dipl.-Ing. Wilhelm Schmidt GmbH

Breslauer Str. 14

64342 Seeheim-Jugenheim

Germany

+49 6257 50 69 0

+49 6257 50 69 50

info@schmidt-seeheim.de

www.schmidt-seeheim.com