

STERILE BOTTLE

Sterile packaging with autoclavable closure

Opening

GL 45 socket (Ø 29 mm opening diameter)

Transport approval

UN 1A1/X2/900

Material

1.4404 (316L)

Finishing

electropolished inside and outside

Volumes

10 ml to 30 liters (see type overview)

Gaskets

PTFE solid part (seal and thread)

Pressure

< 0,5 bar

Closure



GL 45 stainless steel screw cap

- Pressed-in PTFE solid part (thread and seal one piece)
- captive with fixing hose
- completely autoclavable



Type	Material	Finishing	Volume [l]	Ø Da [mm]	H [mm]	s [mm]	Mass [kg]	Pressure [bar]
JM 0.05	1.4404 (316L)	electropolished	0,06	45	75	1	0,15	
JM 0.1	1.4404 (316L)	electropolished	0,12	45	135	1	0,2	
JM 0.25	1.4404 (316L)	electropolished	0,3	67	135	1	0,3	
JM 0.5	1.4404 (316L)	electropolished	0,7	89	170	1	0,5	
JM 01	1.4404 (316L)	electropolished	1,3	108	185	1	0,6	
JM 02	1.4404 (316L)	electropolished	2,8	140	235	1	0,9	
JM 05	1.4404 (316L)	electropolished	6	181	300	1	1,6	
JM 07	1.4404 (316L)	electropolished	8	197	325	1	1,8	
JM 10	1.4404 (316L)	electropolished	12	229	365	1	2,4	
JM 20	1.4404 (316L)	electropolished	22	278	460	1	3,4	
JM 30	1.4404 (316L)	electropolished	32	324	495	1	4,5	

Safety for people, product and the environment



Dipl.-Ing. Wilhelm Schmidt GmbH
 Breslauer Str. 14
 64342 Seeheim-Jugenheim
 Germany

+49 6257 50 69 0
 +49 6257 50 69 50
 info@schmidt-seeheim.de
 www.schmidt-seeheim.com